

Effective removal of light contamination from the material during the screening process: With the compact AIRFIX V 60/VE 60 you can easily add the wind sifting function to your screening machine. Screening and sifting in one pass!

Product Highlights

- Suction/pressure blower with 20.5 kW output
- Can be connected electrically or hydraulically
- Adds wind sifting to the screening process
- Efficient and cost-effective solution

Applications

- Shredded Waste Wood
- Shredded Green Waste
- Shredded Household Waste
- Shredded Commercial Waste > Bark Mulch

What can be removed?

- Shredded Building Rubble
- Shredded Glass s
- Shredded Plastic
- Compost
- Wood Chips
- Grate Ash Soil

- Lightweight Plastics
- Plastic Bags
- Films

Technische Highlights

Convenient Operation

- Easy placement on the ground
- Material transfer into a container
- Regulating slide for volume flow

Versatile in Use

> Practical recesses for easy relocation with a forklift truck

How Does the AIRFIX V 60 Work?

- > The special feature of the AIRFIX is the suction/pressure blower:
- The material is blown under at the end of the discharge belt to make it easier to suck the contaminants upwards.

Can be Used With our Screening Machines





STAR SELECT Star Screen Machines

TERRA SELECT Trommel Screen Machines

	ARFIX V 60	ARFIX VE 60 🥞
Power (kW)	20.5	20.5
Weight (kg)	1,300	1,600
Length (mm)	2,300	2,300
Height (mm)	1,780	1,780
Width (mm)	1,750	1,750

